

0280158677

Injector Deadtime Compensation Table											
Injector Voltage (V)											
bar	8,0	9,0	10,0	11,0	12,0	13,0	14,0	15,0	16,0		
Fuel Pressure	2,5	1,941	1,567	1,277	1,135	1,071	0,973	0,852	0,752	0,723	mS
	3,0	2,048	1,688	1,472	1,237	1,187	0,995	0,879	0,787	0,741	
	3,5	2,318	1,838	1,552	1,319	1,189	1,011	0,918	0,825	0,756	
	4,0	2,618	1,985	1,625	1,361	1,204	1,034	0,935	0,841	0,762	
	4,5	2,833	2,086	1,676	1,445	1,229	1,096	0,949	0,849	0,780	
	5,0	3,366	2,321	1,843	1,508	1,282	1,134	0,957	0,856	0,795	
	5,5		2,660	1,992	1,589	1,336	1,187	1,015	0,906	0,845	
	6,0		3,043	2,169	1,682	1,415	1,270	1,085	0,920	0,858	

Static Flow	
bar	cc/min
2,5	1310
3,0	1455
3,5	1600
4,0	1700
4,5	1800
5,0	1900
5,5	2000
6,0	2100

**Tested with ASNU Test Media at 25°C**

Differential Pressure Compensation	
bar	Factor
2,5	1,11
3,0	1,00
3,5	0,91
4,0	0,85
4,5	0,81
5,0	0,76
5,5	0,72
6,0	0,69

**FINJECTOR.com**