

0280158211

Injector Deadtime Compensation Table											
Injector Voltage (V)											
bar	8,0	9,0	10,0	11,0	12,0	13,0	14,0	15,0	16,0		
Fuel Pressure	2,5	1,677	1,316	1,116	0,952	0,812	0,713	0,588	0,559	0,504	mS
	3,0	1,756	1,422	1,157	0,993	0,862	0,753	0,595	0,567	0,530	
	3,5	1,776	1,469	1,210	0,999	0,876	0,748	0,628	0,559	0,555	
	4,0	1,907	1,470	1,225	1,056	0,890	0,758	0,650	0,591	0,595	
	4,5	1,946	1,538	1,270	1,067	0,941	0,783	0,695	0,640	0,636	
	5,0	2,026	1,575	1,321	1,072	0,946	0,807	0,714	0,646	0,639	
	5,5	2,093	1,642	1,387	1,122	0,959	0,811	0,718	0,649	0,639	
	6,0	2,175	1,678	1,424	1,146	0,965	0,832	0,749	0,662	0,648	

Static Flow		Tested with ASNU Test Media at 25°C
bar	cc/min	
2,5	444	
3,0	495	
3,5	538	
4,0	582	
4,5	612	
5,0	648	
5,5	678	
6,0	712	

Differential Pressure Compensation	
bar	Factor
2,5	1,11
3,0	1,0
3,5	0,92
4,0	0,85
4,5	0,80
5,0	0,76
5,5	0,73
6,0	0,69