

0280158107

Injector Deadtime Compensation Table

Injector Voltage (V)

bar	8,0	9,0	10,0	11,0	12,0	13,0	14,0	15,0	16,0
2,5	1,309	1,071	0,858	0,699	0,565	0,488	0,387	0,314	0,253
3,0	1,361	1,095	0,914	0,723	0,598	0,496	0,427	0,360	0,303
3,5	1,509	1,185	0,976	0,767	0,603	0,550	0,436	0,412	0,326
4,0	1,562	1,188	0,991	0,828	0,631	0,581	0,464	0,436	0,349
4,5	1,580	1,205	1,021	0,872	0,716	0,656	0,493	0,440	0,358
5,0	1,688	1,361	1,092	0,895	0,741	0,679	0,576	0,447	0,384
5,5	1,790	1,383	1,126	0,935	0,807	0,680	0,615	0,466	0,428
6,0	1,866	1,464	1,152	0,976	0,832	0,691	0,632	0,500	0,436

mS

Static Flow

bar	cc/min
2,5	200
3,0	220
3,5	240
4,0	250
4,5	265
5,0	280
5,5	300
6,0	310

Tested with ASNU Test Media at 25°C

Differential Pressure Compensation

bar	Factor
2,5	1,10
3,0	1,00
3,5	0,91
4,0	0,88
4,5	0,83
5,0	0,78
5,5	0,73
6,0	0,71

FINJECTOR.com