RESERVOIRS (3-CHAMBER & 1-CHAMBER)



Features

- > Fiberglass reinforced nylon body
- > Gasket-sealed removable lid allows for easy cleaning
- Reservoir lid features safety screens to prevent foreign objects from falling into chambers
- > Leak-proof baffle design insures that fluid remains in reservoir
- Standard capacity and low profile options available for AN4 type reservoirs

3-Chamber Reservoirs

Incorporates the clutch, front brake and rear brake fluid reservoirs into one convenient package. 2-hole mount provides simple installation onto firewall/bulkhead. The three separate internal chambers allow for complete evacuation of one chamber without affecting the remaining two chambers. Standard capacity reservoirs are available with either hosebarb or AN4 fitting connection. Low profile reservoirs is only available with AN4 fitting connection.

Reservoir Type	Rear Brake Chamber	Front Brake Chamber	Clutch Chamber
Standard Capacity	8.9 oz (263ml)	10.3 oz (313 ml)	4.6 oz (136 ml)
Low Profile	4.0 oz (117ml)	6.1 oz (182 ml)	2.0 oz (59ml)

Description	Part Number
3-chamber reservoir, standard capacity, hose barb connection	72-576
3-chamber reservoir, standard capacity, AN4 connection	72-577
3-chamber reservoir, low profile, AN4 connection	72-578
Hose kit for 72-576 reservoir, includes 96" of hose and 6 hose clamps	72-221
Replacement cap, less baffle	72-576-6
Replacement baffle for cap, funnel type	72-576-4
Replacement lid gasket	72-576-3



Single Chamber Reservoirs

Single chamber reservoirs with 5.3 oz (158 ml) fluid capacity. Available with AN4 fitting for remote-mount applications or with a 15/16"-20 adapter for direct mounting onto Tilton 76-Series master cylinders. Includes filter.

Description	Part Number
3-chamber reservoir, standard capacity, hose barb connection	74-230
3-chamber reservoir, standard capacity, AN4 connection	74-240
Replacement cap	72-207
Replacement filter	74-211