

# EV14-600-L

**Injector Deadtime Compensation Table**

**Injector Voltage (V)**

	bar	8,0	9,0	10,0	11,0	12,0	13,0	14,0	15,0	16,0	
<b>Fuel Pressure</b>	2,5	1,893	1,578	1,357	1,197	1,046	0,920	0,759	0,737	0,667	<b>mS</b>
	3,0	1,955	1,687	1,397	1,151	1,046	0,951	0,809	0,731	0,690	
	3,5	2,117	1,731	1,509	1,241	1,086	1,007	0,885	0,808	0,756	
	4,0	2,250	1,816	1,518	1,343	1,156	1,015	0,923	0,828	0,769	
	4,5	2,316	1,887	1,615	1,355	1,190	1,065	0,933	0,856	0,794	
	5,0	2,437	1,974	1,639	1,418	1,237	1,081	0,940	0,863	0,785	
	5,5	2,601	2,099	1,704	1,449	1,274	1,098	1,034	0,908	0,837	
	6,0	2,829	2,170	1,809	1,569	1,379	1,146	1,067	0,956	0,886	

		bar	cc/min	<b>Tested with ASNU Test Media at 25°C</b>
<b>Fuel Pressure</b>	2,5		522	
	3,0		582	
	3,5		618	
	4,0		672	
	4,5		714	
	5,0		756	
	5,5		810	
	6,0		850	

		bar	Factor
<b>Fuel Pressure</b>	2,5		1,11
	3,0		1,00
	3,5		0,94
	4,0		0,86
	4,5		0,81
	5,0		0,76
	5,5		0,71
	6,0		0,68