

0280158123

Injector Deadtime Compensation Table										
Injector Voltage (V)										
	bar	8,0	9,0	10,0	11,0	12,0	13,0	14,0	15,0	16,0
Fuel Pressure	2,5	1,419	1,179	0,951	0,737	0,647	0,535	0,448	0,423	0,325
	3,0	1,541	1,253	1,025	0,838	0,690	0,606	0,453	0,429	0,394
	3,5	1,669	1,350	1,073	0,876	0,733	0,650	0,496	0,443	0,406
	4,0	1,781	1,404	1,136	0,938	0,739	0,670	0,536	0,457	0,418
	4,5	1,919	1,487	1,203	0,994	0,822	0,680	0,575	0,502	0,500
	5,0	2,023	1,582	1,289	1,011	0,889	0,719	0,630	0,568	0,518
	5,5	2,245	1,718	1,353	1,116	0,945	0,800	0,678	0,591	0,544
	6,0	2,413	1,807	1,438	1,195	0,963	0,860	0,757	0,638	0,574

mS

Static Flow		
	bar	cc/min
Fuel Pressure	2,5	560
	3,0	610
	3,5	660
	4,0	710
	4,5	750
	5,0	820
	5,5	860
	6,0	880

Tested
with
ASNU
Test
Media at
25°C

Differential Pressure Compensation	
bar	Factor
2,5	1,10
3,0	1,00
3,5	0,92
4,0	0,85
4,5	0,81
5,0	0,74
5,5	0,70
6,0	0,69

FINJECTOR.com