

0280158167

Injector Deadtime Compensation Table											
Injector Voltage (V)											
bar	8,0	9,0	10,0	11,0	12,0	13,0	14,0	15,0	16,0		
Fuel Pressure	2,5	1,435	1,127	1,007	0,803	0,662	0,558	0,508	0,419	0,326	mS
	3,0	1,523	1,208	1,060	0,827	0,673	0,563	0,515	0,444	0,349	
	3,5	1,549	1,261	1,073	0,852	0,688	0,612	0,519	0,447	0,355	
	4,0	1,565	1,317	1,078	0,863	0,694	0,624	0,522	0,522	0,369	
	4,5	1,630	1,358	1,098	0,875	0,715	0,629	0,527	0,569	0,374	
	5,0	1,656	1,372	1,104	0,891	0,743	0,650	0,551	0,447	0,389	
	5,5	1,696	1,379	1,112	0,917	0,768	0,660	0,564	0,551	0,399	
	6,0	1,726	1,405	1,118	0,930	0,782	0,692	0,621	0,601	0,405	

Static Flow	
bar	cc/min
2,5	250
3,0	270
3,5	300
4,0	315
4,5	340
5,0	350
5,5	370
6,0	380

Tested with ASNU Test Media at 25°C

Differential Pressure Compensation	
bar	Factor
2,5	1,08
3,0	1,00
3,5	1,11
4,0	1,16
4,5	1,25
5,0	1,29
5,5	1,37
6,0	1,40

FINJECTOR.com