

0280155968

Injector Deadtime Compensation Table

Injector Voltage (V)

bar	8,0	9,0	10,0	11,0	12,0	13,0	14,0	15,0	16,0
2,5	1,321	0,970	0,806	0,642	0,509	0,395	0,340	0,231	0,191
3,0	1,434	1,103	0,851	0,695	0,552	0,460	0,386	0,327	0,223
3,5	1,510	1,197	0,953	0,731	0,582	0,479	0,388	0,371	0,238
4,0	1,638	1,339	1,013	0,818	0,679	0,521	0,418	0,400	0,315
4,5	1,735	1,355	1,074	0,823	0,748	0,577	0,448	0,407	0,327
5,0	1,931	1,457	1,165	0,907	0,782	0,592	0,549	0,413	0,359
5,5	2,077	1,539	1,260	0,995	0,792	0,617	0,550	0,449	0,398
6,0	2,225	1,704	1,339	1,066	0,855	0,682	0,589	0,505	0,410

Static Flow	
bar	cc/min
2,5	400
3,0	450
3,5	490
4,0	520
4,5	550
5,0	580
5,5	610
6,0	640

Tested with ASNU Test Media at 25°C

Differential Pressure Compensation	
bar	Factor
2,5	1,12
3,0	1,00
3,5	0,92
4,0	0,86
4,5	0,82
5,0	0,77
5,5	0,73
6,0	0,70

FINJECTOR.com