

0280158333

Injector Deadtime Compensation Table											
Injector Voltage (V)											
bar	8,0	9,0	10,0	11,0	12,0	13,0	14,0	15,0	16,0		
Fuel Pressure	2,5	1,941	1,567	1,277	1,135	1,071	0,973	0,852	0,752	0,723	mS
	3,0	2,048	1,688	1,472	1,237	1,187	0,995	0,879	0,787	0,741	
	3,5	2,318	1,838	1,552	1,319	1,189	1,011	0,918	0,825	0,756	
	4,0	2,618	1,985	1,625	1,361	1,204	1,034	0,935	0,841	0,762	
	4,5	2,833	2,086	1,676	1,445	1,229	1,096	0,949	0,849	0,780	
	5,0	3,366	2,321	1,843	1,508	1,282	1,134	0,957	0,856	0,795	
	5,5		2,660	1,992	1,589	1,336	1,187	1,015	0,906	0,845	
	6,0		3,043	2,169	1,682	1,415	1,270	1,085	0,920	0,858	

Static Flow		Tested with ASNU Test Media at 25°C
bar	cc/min	
2,5	1310	
3,0	1455	
3,5	1600	
4,0	1700	
4,5	1800	
5,0	1900	
5,5	2000	
6,0	2100	

Differential Pressure Compensation	
bar	Factor
2,5	1,11
3,0	1,00
3,5	0,91
4,0	0,85
4,5	0,81
5,0	0,76
5,5	0,72
6,0	0,69

FINJECTOR.com