

0280158235

Injector Deadtime Compensation Table

Injector Voltage (V)

bar	8,0	9,0	10,0	11,0	12,0	13,0	14,0	15,0	16,0
2,5	2,422	1,873	1,493	1,288	1,095	0,987	0,809	0,765	0,639
3,0	2,705	2,110	1,640	1,378	1,159	0,994	0,900	0,812	0,751
3,5	3,254	2,224	1,751	1,479	1,248	1,050	0,979	0,814	0,800
4,0	3,861	2,480	1,983	1,494	1,279	1,143	1,002	0,876	0,811
4,5		2,668	2,006	1,611	1,370	1,190	1,050	0,910	0,840
5,0		3,015	2,205	1,792	1,454	1,247	1,113	0,973	0,878
5,5			2,378	1,863	1,497	1,281	1,145	1,003	0,885
6,0			2,647	2,033	1,635	1,393	1,157	1,092	0,990

Static Flow	
bar	cc/min
2,5	630
3,0	710
3,5	780
4,0	840
4,5	880
5,0	940
5,5	990
6,0	1040

Tested with ASNU Test Media at 25°C

Differential Pressure Compensation	
bar	Factor
2,5	0,88
3,0	1,00
3,5	1,09
4,0	1,18
4,5	1,23
5,0	1,32
5,5	1,39
6,0	1,46

FINJECTOR.com