

0280158290

Injector Deadtime Compensation Table											
Injector Voltage (V)											
bar	8,0	9,0	10,0	11,0	12,0	13,0	14,0	15,0	16,0		
Fuel Pressure	2,5	2,762	2,081	1,661	1,387	1,252	1,003	0,909	0,823	0,737	mS
	3,0	3,148	2,272	1,816	1,472	1,264	1,051	0,948	0,830	0,766	
	3,5	3,508	2,401	1,878	1,536	1,309	1,128	0,987	0,855	0,825	
	4,0	4,107	2,515	1,974	1,609	1,340	1,178	0,995	0,908	0,853	
	4,5		2,905	2,216	1,732	1,460	1,213	1,060	0,964	0,900	
	5,0		3,270	2,282	1,838	1,498	1,246	1,116	0,990	0,927	
	5,5			2,475	1,993	1,597	1,366	1,207	1,014	0,936	
	6,0			2,940	2,169	1,711	1,422	1,238	1,108	1,020	

Static Flow	
bar	cc/min
2,5	630
3,0	720
3,5	760
4,0	820
4,5	880
5,0	920
5,5	950
6,0	1020

Tested with ASNU Test Media at 25°C

Differential Pressure Compensation	
bar	Factor
2,5	1,14
3,0	1,00
3,5	0,94
4,0	0,87
4,5	0,81
5,0	0,78
5,5	0,75
6,0	0,70

**FINJECTOR.com**