

0280158112

Injector Deadtime Compensation Table

Injector Voltage (V)

bar	8,0	9,0	10,0	11,0	12,0	13,0	14,0	15,0	16,0
2,5	2,235	1,741	1,438	1,243	1,072	0,925	0,816	0,667	0,664
3,0	2,443	1,880	1,544	1,266	1,086	0,969	0,828	0,742	0,681
3,5	2,608	2,023	1,596	1,376	1,183	1,003	0,870	0,800	0,771
4,0	2,928	2,133	1,718	1,435	1,193	1,074	0,956	0,817	0,753
4,5	3,477	2,609	1,855	1,510	1,303	1,123	0,950	0,864	0,778
5,0		2,667	1,962	1,622	1,376	1,204	1,056	0,932	0,838
5,5		2,857	2,098	1,692	1,446	1,240	1,082	1,004	0,918
6,0		3,562	2,342	1,842	1,517	1,327	1,168	1,058	0,942

mS

Static Flow

bar	cc/min
2,5	630
3,0	704
3,5	762
4,0	820
4,5	870
5,0	920
5,5	975
6,0	1020

Tested with ASNU Test Media at 25°C

Differential Pressure Compensation

bar	Factor
2,5	1,12
3,0	1,00
3,5	0,92
4,0	0,85
4,5	0,80
5,0	0,76
5,5	0,72
6,0	0,69

FINJECTOR.com