

		Injector Deadtime Compensation Table Injector Voltage (V)									
_											
	bar	8,0	9,0	10,0	11,0	12,0	13,0	14,0	15,0	16,0	
Fuel Pressure	2,5	1,579	1,258	0,983	0,835	0,688	0,554	0,452	0,392	0,367	-
	3,0	1,612	1,306	1,053	0,839	0,713	0,618	0,524	0,444	0,374	
	3,5	1,684	1 <mark>,34</mark> 3	1,094	0,895	0,742	0,658	0,539	0,432	0,414	
	4,0	1,702	1,395	1,128	0,939	0,814	0,688	0,563	0,499	0,417	mS
	4,5	1,916	1,426	1,207	0,979	0,824	0,703	0,575	0,505	0,440	
	5,0	1,974	1,524	1,210	1,052	0,849	0,733	0,626	0,511	0,445	

	Statio			
	bar	cc/min		
re	2,5	250	Tested with	
Fuel Pressure	3,0	280		
Pre	3,5	300	ASNU	
e e	4,0	315	Test	
4	4,5	340	Media at	
	5,0	355	25°C	

Differential Pressure Compensation		
bar	Factor	
2,5	1,12	
3,0	1,00	
3,5	0,93	
4,0	0,88	
4,5	0,82	
5,0	0,78	

